Wind Solutions Ltd.

HW-ION10K

FEATURES

1. High conversion efficiency.
2. Advanced technology for maximum power point tracking (MPPT).
3. >99% MPPT efficiency.
4. Wide input voltage range.
5. Without transformer.
6. Protection against reverse polarity, voltage surges, short circuits.
7. Powerful communication interfaces.
8. Integrated data logger available.
9. Easy operation and installation
10. Easy-to-set multilingual LCD display.

HW-ION10K HW-ION10K HW-ION10K
HW-ION10K HW-ION10K HW-ION10K
HW-ION10K HW-ION10K HW-ION10K
HW-ION10K HW-ION10K HW-ION10K
HW-ION10K HW-ION10K HW-ION10K
HW-ION10K HW-ION10K HW-ION10K
HW-ION10K HW-ION10K HW-ION10K
HW-ION10K HW-ION10K HW-ION10K

DC INPUT	
Recommended Generator Rated Power	5kW
DC input voltage range	200~450Vdc
Ma x. input current	65A

AC OUTPUT	
Max. output power	13kW
Nominal output power	10kW
Current THD (at nominal power)	< 3 %
Nominal grid-voltage	180~260Vac
Nominal output current	43.5A
Nominal grid- frequency	50Hz / 60Hz
Power Factor (at nominal power)	>0.99

SYSTEM	
Max Efficiency	94.5 %
Europe Efficiency	93.5 %
Protection degree	IP20(indoor)
Operation temperature	-20°C~+40°C
Cooling method	Natural cooling
Relative humidity	0~95% non condensing
Recommended controller	WEL-10K
Display	LCD
Communication interfaces (optional)	RS485 Ethernet / GPRS

MECHANICAL DATA	
Size: W | H | D (mm)	530 x 900 x 460
Weight	200kg

Wind Solutions Ltd. / Tel: 519-289-2726 E-mail: sales@windsolutions.ca
P.O. BOX 20004 Suite 78, Front Street East Strathroy, Ontario, Canada. N7G 4L6