Wind Solutions Ltd.

HW-ION20K

FEATURES

1. High conversion efficiency.
2. Advanced technology for maximum power point tracking (MPPT).
3. >99% MPPT efficiency.
4. Wide input voltage range.
5. Without transformer.
6. Protection against reverse polarity, voltage surges, short circuits.
7. Powerful communication interfaces.
8. Integrated data logger available.
9. Easy operation and installation
10. Easy-to-set multilingual LCD display.

HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20
HW-ION20K HW-ION20
HW-ION20K HW-ION20
HW-ION20K HW-ION20
HW-ION20K HW-ION20
HW-ION20K HW-ION20
HW-ION20K HW-ION20
HW-ION20K HW-ION20
HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K HW-ION20K
HW-ION20K HW-ION20K HW-ION20K HW-ION20K

DC INPUT	
Recommended Generator Rated Power	10kW
DC input voltage range	200~800Vdc
Ma x. input current	100A

AC OUTPUT	
Max. output power	26kW
Nominal output power	20kW
Current THD (at nominal power)	< 3 %
Nominal grid-voltage	180~260Vac
Nominal output current	87A
Nominal grid- frequency	50Hz / 60Hz
Power Factor (at nominal power)	>0.99

SYSTEM	
Max Efficiency	94.5 %
Europe Efficiency	93.5 %
Protection degree	IP20(outdoor)
Operation temperature	-20°C~+40°C
Cooling method	Natural cooling
Relative humidity	0~95% non condensing
Recommended controller	WEL-20K
Display	LCD
Communication interfaces (optional)	RS485 Ethernet / GPRS

MECHANICAL DATA	
Size: W | H | D (mm)	820x1964x646
Weight	400kg

Wind Solutions Ltd. / Tel: 519-289-2726 E-mail: sales@windsolutions.ca
P.O. BOX 20004 Suite 78, Front Street East Strathroy, Ontario, Canada. N7G 4L6