Wind Solutions Ltd.

HW-ION3K

FEATURES

1. High conversion efficiency.
2. Advanced technology for maximum power point tracking (MPPT).
3. >99% MPPT efficiency.
4. Wide input voltage range.
5. Without transformer.
6. Protection against reverse polarity, voltage surges, short circuits.
7. Powerful communication interfaces.
8. Integrated data logger available.
9. Easy operation and installation
10. Easy-to-set multilingual LCD display.

DC INPUT	
Recommended Generator Rated Power	2kW
DC input voltage range	200~450Vdc
Ma x. input current	18A

AC OUTPUT	
Max. output power	3600 W
Nominal output power	3kW
Current THD (at nominal power)	< 3 %
Nominal grid-voltage	180~260Vac
Nominal output current	13A
Nominal grid- frequency	50Hz / 60Hz
Power Factor (at nominal power)	>0.99

SYSTEM	
Max Efficiency	94 %
Europe Efficiency	93 %
Protection degree	IP65(outdoor)
Operation temperature	-25°C~+60°C
Cooling method	Natural cooling
Relative humidity	0~95% non condensing
Recommended controller	WEL-4K
Display	LCD
Communication interfaces (optional)	RS485 Ethernet / GPRS

MECHANICAL DATA	
Size: W | H | D (mm)	490 x 380 x 177
Weight	44.0kg

Wind Solutions Ltd. / Tel: 519-289-2726 E-mail: sales@windsolutions.ca
P.O. BOX 20004 Suite 78, Front Street East Strathroy, Ontario, Canada. N7G 4L6