Wind Solutions Ltd.

HW-ION50K3

FEATURES

1. High conversion efficiency.
2. Advanced technology for maximum power point tracking (MPPT).
3. >99% MPPT efficiency.
4. Wide input voltage range.
5. Without transformer.
6. Protection against reverse polarity, voltage surges, short circuits.
7. Powerful communication interfaces.
8. Integrated data logger available.
9. Easy operation and installation
10. Easy-to-set multilingual LCD display.

WIND TURBINE HW-ION50K3 HW-ION50K3
WIND TURBINE HW-ION50K3 HW-ION50K3
WIND TURBINE HW-ION50K3 HW-ION50K3
WIND TURBINE HW-ION50K3 HW-ION50K3
WIND TURBINE HW-ION50K3 HW-ION50K3
WIND TURBINE HW-ION50K3 HW-ION50K3
WIND TURBINE HW-ION50K3 HW-ION50K3
WIND TURBINE HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3 HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3 HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3 HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3 HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3 HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3 HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3 HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3 HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3 HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3 HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3 HW-ION50K3 HW-ION50K3
HW-ION50K3 HW-ION50K3 HW-ION50K3 HW-ION50K3

DC INPUT	
Recommended Generator Rated Power	25kW
DC input voltage range	400~850Vdc
Ma x. input current	137A

AC OUTPUT	
Max. output power	To be asked
Nominal output power	50kW
Current THD (at nominal power)	< 3 %
Nominal grid-voltage	330~450Vac
Nominal output current	72.2A
Nominal grid- frequency	50Hz / 60Hz
Power Factor (at nominal power)	>0.99

SYSTEM	
Max Efficiency	95 %
Europe Efficiency	94 %
Protection degree	IP20(indoor)
Operation temperature	-20°C~+40°C
Cooling method	Natural cooling
Relative humidity	0~95% non condensing
Recommended controller	To be asked
Display	LCD
Communication interfaces (optional)	RS485 Ethernet / GPRS

MECHANICAL DATA	
Size: W | H | D (mm)	820x1964x646
Weight	700kg

Wind Solutions Ltd. / Tel: 519-289-2726 E-mail: sales@windsolutions.ca
P.O. BOX 20004 Suite 78, Front Street East Strathroy, Ontario, Canada. N7G 4L6